

RYSTIX SALES c.c.
Timber treatment specialists

PRODUCT DESCRIPTION AND APPLICATION INSTRUCTIONS

RYSTIX TIMBACARE®

Additive for exterior sealer – “AFS”

PRODUCT DESCRIPTION

A technically advanced synthetic urethane hardening agent for use with Timbacare exterior sealer.

This specially formulated polymer greatly improves the durability, hardness and chemical resistance of the sealer while at the same time speeding up the drying time.

Timbacare is AFS is recommended for addition to the exterior sealer when applying to surfaces subject to heavy wear and tear such as decks, walkways, stairs, railings and all outdoor furniture.

Timbacare AFS is a clear water-like liquid.

APPLICATION

Recommended for addition at 10 to 20% by volume to Timbacare exterior sealer.

Mix only enough for immediate application as the mixture will thicken with time.

Do not mix more than is to be applied within two to three hours.

Mix thoroughly by shaking before commencing application.

Any remaining of the mixture should be used up since it will thicken with time and become too thick to apply.

It is not necessary to use AFS when applying sealer to vertical surfaces or horizontal surfaces not subject to wear and tear.

Refer to the technical data sheet on the exterior sealer for full instructions on how and when to apply the sealer.

IMPORTANT **The container of AFS should be kept tightly sealed at all times when not in use.**

CLEANING Clean brushes and other equipment with lacquer thinners immediately after use. A mixture of mineral turpentine and lacquer thinners is also quite suitable.

CAUTION – SAFETY

Avoid inhalation of vapour as well as eye and skin contact. In the event of accidental contact, wash skin with copious amounts of soap and water; flush eyes with an eyewash solution and copious amounts of water and consult a physician. If swallowed induce vomiting and consult a physician immediately.

KEEP OUT OF THE REACH OF CHILDREN

June 2000