MATERIAL SAFETY DATA SHEET

PRODUCT:

SEALER COLOURED

Conforms to ISO 11014-1

1. Product and Company Identification

1866

Commercial name of Product:

UN Number:

Manufacturer:

Chemicals & Research cc, 12 Regents Avenue, Anzac, BRAKPAN SEALER COLOURED

Mixture

C.A.S. number:

Supplier:

Rystix Sales CC P O Box 1053 PORT ELIZABETH 6000

Emergency telephone number: +27 41 365 7172

Fax no: +27 41 365 6973

2. Composition/Information on ingredients

Substance/preparation:

Preparation

Information on hazardous ingredients

Chemical name	CAS No.	%	Symbol	R-Phrases
Low aromatic white spirit	63394-00-3	40 - 50	F	R10, R16, R18, R20/21/22
Aromatic solvent		2 – 8	F	R10, R16, R18, R20/21/22

Occupational exposure limits, if available, are listed in section 8.

3. Hazards identification

Physical/chemical hazards:

Human health hazards:

Environmental hazards:

First aid measures

4.

Flammable. Explosive when mixed with oxidizing substances. In use may form flammable/explosive air/vapour mixtures.

Harmful by inhalation, in contact with the skin and if ingested. Irritating to the eyes.

Harmful to aquatic organisms.

Effects and symptoms		
Inhalation:	Slightly hazardous by inhala	tion (lung irritant).
Ingestion:	Slightly hazardous if ingeste	d.
Skin contact:	Slightly hazardous in case of	f skin contact (irritant, sensitizer).
Eye contact:	Slightly hazardous in case of	f eye contact (corrosive, irritant).
Aggravating conditions:	None known.	
First aid measures		
Inhalation:	Allow exposed persons to re	est in a well-ventilated area.
Ingestion:	Do not induce vomiting. Rin: obtain medical attention.	se out mouth with copious quantities of water and
Skin contact:	Wash contaminated skin wit	h water and soap.
Continued on next page	Version: 2.	Page no. 1 of 5.

PRODUCT:

SEALER COLOURED

Eve contact:

Note to Physician:

Protection of first-aiders:

5. Fire fighting measures

Suitable extinguishing media:

Special fire-fighting procedures:

Unusual/explosion hazards:

Hazardous thermal decomposition **Products:**

Protection of fire-fighters:

6. Accidental release measures

Personal Precautions:

Environmental precautions And clean-up methods:

7. Handling and storage

Handling:

Storage:

Use chemical resistant gloves to protect hands, together with splash goggles.

Suitable packaging materials:

Sturdy metal containers.

Explosion controls/Personal protection 8.

Engineering controls:

Provide adequate ventilation. Ensure that the correct type of eye wash station is in the vicinity of the work place.

Hygiene measurers:

Occupational exposure limits:

Wash hands before leaving the work place.

Hazardous ingredients TLV/PEL TWA: 200 ppm from ACGIH (1997) Inhalation, Respirable. Low aromatic white spirit TWA: 100 ppm from ACGIH (1997) Inhalation, Respirable Aromatic solvent

Check for and remove contact lenses and rinse the eyes with clean water. Obtain medical attention.

Treat symptomatically.

Wear a surgical mask and latex gloves.

Small fire: use dry powder, Large fire: use alcohol resistant foam, never use strong water jets.

Remove unaffected containers, if safe. Keep all persons up-wind from fire.

Unopened containers may explode if subjected to fire.

Oxides of Carbon.

Fire fighters should wear full turn-out gear and correct type respirators.

Splash goggles, gloves, boots, respirator, full suit.

Do not allow spilt material to enter sewers or streams. Dyke in if necessary. Absorb spilt material onto a suitable absorbant and dispose of in an approved dump.

Store in a cool, dry place away from heat and sources of ignition

PRODUCT: SEALER COLOURED

9. Physical and Chemical properties

Physical state and appearance:	Clear homogenous free-flowing liquid.
Colour:	Colourless to dark straw.
Odour threshold:	Not available.
Boiling point:	>125°C.
Melting point:	<0°C.
Bulk density:	0,86 @ 20°C.
Vapour density:	Not available.
Vapour pressure:	Not available.
Evaporation rate:	>1 (Butyl Acetate =1)
Solubility:	Soluble in solvents only.
Octanol/water partition coefficient:	The product is more soluble in oil than in water.
pH:	N.A.
Flashpoint:	38°C (PMCC).
Flammability:	Flammable.
Auto ignition point:	Not known
Explosion properties:	Highly explosive in presence of fire and sparks. Explosive in presence of heat.
Viscosity:	N.A.
Stability and reactivity	

Stability:

10

L

Conditions to avoid/ materials to avoid:

Hazardous reactions:

Hazardous decomposition products:

Product is stable.

Exposure to temperatures >60°C should be avoided. Exposure to acids is to be prevented.

None known.

Oxides of Carbon.

Continued on next page	Version: 2.	Page no. 3 of 5.

PRODUCT: SEALER COLOURED

11. Toxicological information

	Acute data [LD50, LC50] Toxicity to test animals:	Acute oral toxicity for product > 2700 for Aromatic solvent [Rat].
	Local effects:	
	Skin irritation:	Non-corrosive to the skin.
	Eye irritation:	Slightly hazardous in case of eye contact (irritant).
	Sensitization:	Slightly hazardous in case of skin contact (sensitizer).
	Chronic toxicity:	None known.
	Specific effects:	
	Carcinogenic effects:	None known.
	Mutagenic effects:	Not available.
	Reproduction effects:	Not available.
12.	Ecological information	
	Mobility:	Slightly mobile in nature.
	Persistence/degradability:	Product is not freely biodegradable.
	Bioaccumulation potential:	Unknown.
	Ecotoxicity:	Product is harmful to aquatic organisms.
13.	Disposal considerations	
	Methods of disposal	
	Waste or residues	Dispose of in accordance with national legislative requirements.
	Contaminated packaging:	Dispose of in accordance with national legislative requirements.
14.	Transport information	
	International transport regulations	
	UN number:	1866
	Land - Road/Railway:	
	Proper shipping name:	Resin solution, flammable n.o.s. (Low aromatic white spirit & Aromatic solvent).
	ADR/RID class:	3.
	ADR/RID item number:	3.3
	Packing group:	b.
	Hazard identification number:	Not available.
	ADR/RID label:	F

Continued on next page	Version: 2.	Page no. 4 of 5.

PRODUCT: SEALER COLOURED

Sea:

Proper shipping name:	Resin solution, flammable n.o.s. (Low aromatic white spirit & Aromatic solvent).
IMDG Class:	3.3
IMDG page no.:	3279
IMDG label:	F
Medical First Aid Guide [MFAG]:	310
Emergency Schedule [EmS]:	3-05
Marine pollutant:	P

<u>Air</u>:

Proper shipping name:	Resin solution, flammable n.o.s. (Low aromatic white spirit & Aromatic solvent).
UN/ID no.:	1866
IATA-DGR Class:	Not available.
IATA label:	F

15. <u>Regulatory information</u>

Hazard symbols:	F, P	
Risk phrases:	R10 R16 R18 R20/21/22	Flammable, Explosive when mixed with oxidizing substances, In use it may form flammable/explosive air/vapour mixtures, Harmful by inhalation, in contact with the skin and if inhaled,
Safety phrases:	S2 S13 S46	Keep out of reach of children, Keep away from food, drink and animal foodstuffs. If ingested seek medical attention and show this document,
Child protection:	Prevent children a	access to this product.
Contains:	Low aromatic whit Aromatic solvent.	te spirit,

16. Other information

History	
Date of issue:	2018.10.21
Version:	2.
E. & O.E.	

NOTICE TO READER

DISCLAIMER

To the best of our knowledge the information contained herein is accurate.

However, neither the compiler nor the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

|--|