

# MATERIAL SAFETY DATA SHEET

Conforms to ISO 11014-1

## PRODUCT: INTERIOR COATINGS (PU)

### 1. Product and Company Identification

Commercial name of Product: **INTERIOR COATING**  
UN Number: **1866** C.A.S. number: Mixture

**Manufacturer:** **Chemicals & Research cc,**  
12 Regents Avenue,  
Anzac,  
**BRAKPAN**

**Supplier:** **Rystix Sales cc**  
P O Box 1053  
Port Elizabeth  
**6000**

**Emergency telephone number: +27 41 365 7172 Fax no: +27 41 365 6973**

### 2. Composition/Information on ingredients

Substance/preparation: Preparation  
Information on hazardous ingredients

Chemical name	CAS No.	%	Symbol	R-Phrases
Low aromatic white spirit	63394-00-3	25 – 30	F	R10, R16, R18, R20/21/22
Aromatic solvent		20 – 25	F	R10, R16, R18, R20/21/22
Zirconium Octoate	15104-99-1	0.15	Xi	R10, R22-R36/R38-R43
Calcium Octoate	136-51-6	0.20	Xi	R10, R22-R36/R38-R43
Cobalt Octoate	36-57-7	0.05	Xi	R10, R22-R36/R38-R43

Occupational exposure limits, if available, are listed in section 8.

### 3. Hazards identification

Physical/chemical hazards: Flammable.  
Explosive when mixed with oxidizing substances.  
In use may form flammable/explosive air/vapour mixtures.

Human health hazards: Harmful by inhalation, in contact with the skin and if ingested.  
Irritating to the eyes.

Environmental hazards: Harmful to aquatic organisms.

### 4. First aid measures

#### Effects and symptoms

Inhalation: Slightly hazardous by inhalation (lung irritant).  
Ingestion: Slightly hazardous if ingested.  
Skin contact: Slightly hazardous in case of skin contact (irritant, sensitizer).  
Eye contact: Slightly hazardous in case of eye contact (corrosive, irritant).  
Aggravating conditions: None known.

#### First aid measures

Inhalation: Allow exposed persons to rest in a well-ventilated area.  
Ingestion: Do not induce vomiting. Rinse out mouth with copious quantities of water and obtain medical attention.  
Skin contact: Wash contaminated skin with water and soap.

# **PRODUCT: INTERIOR COATINGS (PU)**

Eye contact: Check for and remove contact lenses and rinse the eyes with clean water. Obtain medical attention.

Note to Physician: Treat symptomatically.

Protection of first-aiders: Wear a surgical mask and latex gloves.

## **5. Fire fighting measures**

Suitable extinguishing media: Small fire: use dry powder,  
Large fire: use alcohol resistant foam, never use strong water jets.

Special fire-fighting procedures: Remove unaffected containers, if safe.  
Keep all persons up-wind from fire.

Unusual/explosion hazards: Unopened containers may explode if subjected to fire.

Hazardous thermal decomposition Products: Oxides of Carbon.

Protection of fire-fighters: Fire fighters should wear full turn-out gear and correct type respirators.

## **6. Accidental release measures**

Personal Precautions: Splash goggles, gloves, boots, respirator, full suit.

Environmental precautions And clean-up methods: Do not allow spilt material to enter sewers or streams. Dyke in if necessary. Absorb spilt material onto a suitable absorbant and dispose of in an approved dump.

## **7. Handling and storage**

Handling: Use chemical resistant gloves to protect hands, together with splash goggles.

Storage: Store in a cool, dry place away from heat and sources of ignition

Suitable packaging materials: Sturdy metal containers.

## **8. Explosion controls/Personal protection**

Engineering controls: Provide adequate ventilation.  
Ensure that the correct type of eye wash station is in the vicinity of the work place.

Hygiene measurers: Wash hands before leaving the work place.

Occupational exposure limits:

<b>Hazardous ingredients</b>	<b>TLV/PEL</b>
Low aromatic white spirit	TWA: 200 ppm from ACGIH (1997) Inhalation, Respirable.
Aromatic solvent	TWA: 100 ppm from ACGIH (1997) Inhalation, Respirable

## **PRODUCT: INTERIOR COATINGS (PU)**

### **9. Physical and Chemical properties**

Physical state and appearance:	Clear homogenous free-flowing liquid.
Colour:	Colourless to dark straw.
Odour threshold:	Not available.
Boiling point:	>125°C.
Melting point:	<0°C.
Bulk density:	0,86 @ 20°C.
Vapour density:	Not available.
Vapour pressure:	Not available.
Evaporation rate:	>1 (Butyl Acetate =1)
Solubility:	Soluble in solvents only.
Octanol/water partition coefficient:	The product is more soluble in oil than in water.
pH:	N.A.
Flashpoint:	38°C (PMCC).
Flammability:	Flammable.
Auto ignition point:	Not known
Explosion properties:	Highly explosive in presence of fire and sparks. Explosive in presence of heat.
Viscosity:	N.A.

### **10 Stability and reactivity**

Stability:	Product is stable.
Conditions to avoid/ materials to avoid:	Exposure to temperatures >60°C should be avoided. Exposure to acids is to be prevented.
Hazardous reactions:	None known.
Hazardous decomposition products:	Oxides of Carbon.

# **PRODUCT: INTERIOR COATINGS (PU)**

## **11. Toxicological information**

Acute data [LD50, LC50]  
Toxicity to test animals:

Acute oral toxicity for product > 2700 for Aromatic solvent [Rat].

### **Local effects:**

Skin irritation:

Non-corrosive to the skin.

Eye irritation:

Slightly hazardous in case of eye contact (irritant).

Sensitization:

Slightly hazardous in case of skin contact (sensitizer).

Chronic toxicity:

None known.

### **Specific effects:**

Carcinogenic effects:

None known.

Mutagenic effects:

Not available.

Reproduction effects:

Not available.

## **12. Ecological information**

Mobility:

Slightly mobile in nature.

Persistence/degradability:

Product is not freely biodegradable.

Bioaccumulation potential:

Unknown.

Ecotoxicity:

Product is harmful to aquatic organisms.

## **13. Disposal considerations**

### **Methods of disposal**

Waste or residues

Dispose of in accordance with national legislative requirements.

Contaminated packaging:

Dispose of in accordance with national legislative requirements.

## **14. Transport information**

### **International transport regulations**

**UN number:**

**1866**

Land - Road/Railway:

Proper shipping name:

Resin solution, flammable n.o.s. (Low aromatic white spirit & Aromatic solvent).

ADR/RID class:

3.

ADR/RID item number:

3.3

Packing group:

b.

Hazard identification number:

Not available.

ADR/RID label:

F

## PRODUCT: INTERIOR COATINGS (PU)

### Sea:

Proper shipping name:	Resin solution, flammable n.o.s. (Low aromatic white spirit & Aromatic solvent).
IMDG Class:	3.3
IMDG page no.:	3279
IMDG label:	F
Medical First Aid Guide [MFAG]:	310
Emergency Schedule [EmS]:	3-05
Marine pollutant:	P

### Air:

Proper shipping name:	Resin solution, flammable n.o.s. (Low aromatic white spirit & Aromatic solvent).
UN/ID no.:	<b>1866</b>
IATA-DGR Class:	Not available.
IATA label:	F

## 15. Regulatory information

Hazard symbols:	F, P
Risk phrases:	R10 Flammable, R16 Explosive when mixed with oxidizing substances, R18 In use it may form flammable/explosive air/vapour mixtures, R20/21/22 Harmful by inhalation, in contact with the skin and if inhaled, R36/38 Irritation to eyes and skin, R43 May cause sensitivity by skin contact,
Safety phrases:	S2 Keep out of reach of children, S13 Keep away from food, drink and animal foodstuffs, S46 If ingested seek medical attention and show this document,
Child protection:	Prevent children access to this product.
Contains:	Low aromatic white spirit, Aromatic solvent.

## 16. Other information

### History

Date of printing:	2005.06.23
Date of issue:	2005.06.23
Version:	2.

### **E. & O.E.**

### NOTICE TO READER

### Disclaimer

*To the best of our knowledge the information contained herein is accurate.*

*However, neither the compiler nor the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.*