

5mm

WARRANTY

All information is based upon current knowledge and experience and is given in good faith. While all Rystix Timbacare products are manufactured to the highest quality standards, and since they may be stored, handled and used under conditions which are beyond our control, we cannot accept responsibility for any direct or consequential loss suffered, how so ever this should arise, from the use of our products. Active technical service and advice forms an integral part of our service and customers are encouraged to make use of this in optimising the performance of Rystix Timbacare under their particular conditions.

Caution:

Keep out of the reach of children. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, seek medical advice immediately and show safety data sheet.

Use only in well ventilated areas. For best results do not coat in temperatures below 5°C or above 30°C. Do not store product in frosty conditions or where temperatures are below 0°C for any length of time.

Ensure lid is properly sealed after use to prevent skin forming, we advise storing in a smaller container should liquid content be less than half of existing container



EU limit value for this product (cat.A/f): 700g/l (2010)
This product contains max 460g/l VOC

Methods of disposal

Waste or residues / Contaminated packaging
Dispose of in accordance with national legislative requirements.

This product is marketed and distributed by:

SOUTH AFRICA
Rystix Sales CC

P O Box 1053, Port Elizabeth, 6000
Local Tel: 0861 RYSTIX (797849)
Int'l Tel: +27 41 3657172 (office hrs)
info@rystix.co.za | www.rystix.co.za

STIR WELL BEFORE USE

Rystix®

INTERIOR POLYFLOOR

Tough, Wear Resistant
Polyurethane Floor Coating

FOR PEOPLE WHO LOVE WOOD**5L****RYSTIX TIMBACARE POLYURETHANE FLOORCOAT**

This clear, fast-drying universal Polyurethane floor coating is highly recommended for use on all interior wooden floors, table and counter tops and is available in a tough gloss or eggshell sheen variant.

Application Directions: Remove any old coatings with a quality paint stripper, or by sanding and/or scraping, taking care to remove any oily or fatty deposits using a strong solvent. Ensure all surfaces to be coated are clean and dry before coating. Finish wood with fine sandpaper in the direction of the grain and ensure all dust is removed from the surface and the spaces between floorboards before coating.

This product should NOT be diluted at all!

Important: Lightly apply 3 or more undiluted coats using a clean good quality long-bristle brush for best results. Heavy application could result in brush drag marks or bubbling in the product. It is possible to apply using a good quality squeegee provided care is taken to avoid premature drying.

Allow sufficient time for the first coat to be dry (2 to 4 hours depending on ambient conditions) before lightly sanding with the finest grade sandpaper to remove any raised fibres. Apply second and third coats as soon as earlier coats are dry and avoid allowing more than one day between coats. On freshly-sanded porous timber it may be necessary to apply more than 3 coats. Care should be taken to remove any dust which may settle between coats.

If a coloured floor is required, it is recommended that the floor be tinted prior to application of **Timbacare Interior Polyfloor** since it is easier to maintain a clear top coating than to try and colour match at a later stage due to wear and tear. Quality universal tints may be added to the product if desired following the manufacturer's specification according to the colour required.

Application rate: Approximately 10-15 square metres per litre per coat, depending on the porosity of the timber.

Caution: Storage should be in a tightly closed container at all times. Avoid storing half-empty containers and remove any traces of spill around the lip of the tin before replacing the lid.

Cleaning: To prevent the product hardening rapidly on the paint brushes and other equipment, clean immediately after use with lacquer thinners or white spirit based brush cleaner. Mineral turpentine may be used with this product.

Safety: Rystix Timbacare contains flammable solvents and should be kept away from open flames. Store in a cool safe place out of the reach of children. Ensure adequate ventilation while applying indoors or in confined areas.

STEEL PACK

DATE: 14/09/2022
CUSTOMER: RYSTIX
DESCRIPTION:
Rystix Timbacare Polyurethane Floorcoat
SIZE: 5L

COLOURS:

- BROWN
- PANTONE 527C
- BLACK
- CYAN
- WORKS MAP
- CMYK

Code: 2733
Sample No: 583

PLEASE CHECK BEFORE YOU SIGN!

SIGNATURE

PRINT NAME

Peter D Ryder

DATE

20/09/2022